

February 1988

MM70C95/MM80C95, MM70C97/MM80C97  
TRI-STATE® Hex Buffers  
MM70C96/MM80C96, MM70C98/MM80C98  
TRI-STATE Hex Inverters

General Description

These gates are monolithic complementary MOS (CMOS) integrated circuits constructed with N- and P-channel enhancement mode transistors. The MM70C95/MM80C95 and the MM70C97/MM80C97 convert CMOS or TTL outputs to TRI-STATE outputs with no logic inversion, the MM70C96/MM80C96 and the MM70C98/MM80C98 provide the logical opposite of the input signal. The MM70C95/MM80C95 and the MM70C96/MM80C96 have common TRI-STATE controls for all six devices. The MM70C97/MM80C97 and the MM70C98/MM80C98 have two TRI-STATE controls; one for two devices and one for the other four devices. Inputs are protected from damage due to static discharge by diode clamps to  $V_{CC}$  and GND.

Features


- Wide supply voltage range 3.0V to 15V
- Guaranteed noise margin 1.0V
- High noise immunity 0.45  $V_{CC}$  (typ.)
- TTL compatible Drive 1 TTL Load

Applications

- Bus drivers Typical propagation delay into 150 pF load is 40 ns

Connection Diagrams (Dual-In-Line Packages)

MM70C95/MM80C95




TL/F/5907-1

Top View

Order Number MM70C95 or MM80C95

MM70C96/MM80C96




TL/F/5907-2

Top View

Order Number MM70C96 or MM80C96

MM70C97/MM80C97




TL/F/5907-3

Top View

Order Number MM70C97 or MM80C97

MM70C98/MM80C98



TL/F/5907-4

Top View

Order Number MM70C98 or MM80C98

TRI-STATE® is a registered trademark of National Semiconductor Corporation.

MM70C95/MM80C95, MM70C97/MM80C97 TRI-STATE Hex Buffers  
MM70C96/MM80C96, MM70C98/MM80C98 TRI-STATE Hex Inverters

## Absolute Maximum Ratings (Note 1)

If Military/Aerospace specified devices are required, please contact the National Semiconductor Sales Office/Distributors for availability and specifications.

Voltage at Any Pin	−0.3V to $V_{CC} + 0.3V$
Operating Temperature Range	−55°C to +125°C
MM70CXX	−40°C to +85°C
MM80CXX	

Storage Temperature Range	−65°C to +150°C
Power Dissipation ( $P_D$ )	
Dual-In-Line	700 mW
Small Outline	500 mW
Power Supply Voltage ( $V_{CC}$ )	18V
Lead Temperature	
(Soldering, 10 seconds)	260°C

## DC Electrical Characteristics Min/Max limits apply across temperature range unless otherwise noted

Symbol	Parameter	Conditions	Min	Typ	Max	Units
<b>CMOS TO CMOS</b>						
$V_{IN(1)}$	Logical “1” Input Voltage	$V_{CC} = 5V$ $V_{CC} = 10V$	3.5 8.0			V V
$V_{IN(0)}$	Logical “0” Input Voltage	$V_{CC} = 5V$ $V_{CC} = 10V$			1.5 2.0	V V
$V_{OUT(1)}$	Logical “1” Output Voltage	$V_{CC} = 5V$ $V_{CC} = 10V$	4.5 9.0			V V
$V_{OUT(0)}$	Logical “0” Output Voltage	$V_{CC} = 5V$ $V_{CC} = 10V$			0.5 1.0	V V
$I_{IN(1)}$	Logical “1” Input Current	$V_{CC} = 15V$		0.005	1.0	$\mu A$
$I_{IN(0)}$	Logical “0” Input Current		−1.0	−0.005		$\mu A$
$I_{OZ}$	Output Current in High Impedance State	$V_{CC} = 15V, V_O = 15V$ $V_{CC} = 15V, V_O = 0V$	−1.0	0.005 −0.005	1.0	$\mu A$ $\mu A$
$I_{CC}$	Supply Current	$V_{CC} = 15V$		0.01	15	$\mu A$

## TTL INTERFACE

$V_{IN(1)}$	Logical “1” Input Voltage	70C $V_{CC} = 4.5V$ 80C $V_{CC} = 4.75V$	$V_{CC} - 1.5$ $V_{CC} - 1.5$			V V
$V_{IN(0)}$	Logical “0” Input Voltage	70C $V_{CC} = 4.5V$ 80C $V_{CC} = 4.75V$			0.8 0.8	V V
$V_{OUT(1)}$	Logical “1” Output Voltage	70C $V_{CC} = 4.5V, I_O = -1.6 mA$ 80C $V_{CC} = 4.75V, I_O = -1.6 mA$	2.4 2.4			V V
$V_{OUT(0)}$	Logical “0” Output Voltage	70C $V_{CC} = 4.5V, I_O = 1.6 mA$ 80C $V_{CC} = 4.75V, I_O = 1.6 mA$			0.4 0.4	V V

## OUTPUT DRIVE (Short Circuit Current)

$I_{SOURCE}$	Output Source Current	$V_{CC} = 5V, V_{IN(1)} = 5V$ $T_A = 25^\circ C, V_{OUT} = 0V$	−4.35			mA
$I_{SOURCE}$	Output Source Current	$V_{CC} = 10V, V_{IN(1)} = 10V$ $T_A = 25^\circ C, V_{OUT} = 0V$	−20			mA
$I_{SINK}$	Output Sink Current	$V_{CC} = 5V, V_{IN(0)} = 0V$ $T_A = 25^\circ C, V_{OUT} = V_{CC}$	4.35			mA
$I_{SINK}$	Output Sink Current	$V_{CC} = 10V, V_{IN(0)} = 0V$ $T_A = 25^\circ C, V_{OUT} = V_{CC}$	20			mA

**Note 1:** “Absolute Maximum Ratings” are those values beyond which the safety of the device cannot be guaranteed. Except for “Operating Temperature Range” they are not meant to imply that the device should be operated at these limits. The table of “Electrical Characteristics” provides conditions for actual device operation.

**Note 2:** Capacitance is guaranteed by periodic testing.

**Note 3:**  $C_{PD}$  determines the no load AC power consumption of any CMOS device. For complete explanation see 54C/74C Family Characteristics application note AN-90.

## AC Electrical Characteristics\* $T_A = 25^\circ\text{C}$ , $C_L = 50\text{ pF}$ , unless otherwise noted.

Symbol	Parameter	Conditions	Min	Typ	Max	Units
$t_{pd0}$ , $t_{pd1}$	Propagation Delay Time to a Logical "0" or Logical "1" from Data Input to Output MM70C95/MM80C95, MM70C97/MM80C97 MM70C96/MM80C96, MM70C98/MM80C98	$V_{CC} = 5\text{V}$ $V_{CC} = 10\text{V}$ $V_{CC} = 5\text{V}$ $V_{CC} = 10\text{V}$		60 25 70 35	100 40 150 75	ns ns ns ns
$t_{pd0}$ , $t_{pd1}$	Propagation Delay Time to a Logical "0" or Logical "1" from Data Input to Output MM70C95/MM80C95, MM70C97/MM80C97 MM70C96/MM80C96, MM70C98/MM80C98	$V_{CC} = 5\text{V}$ , $C_L = 150\text{ pF}$ $V_{CC} = 10\text{V}$ , $C_L = 150\text{ pF}$ $V_{CC} = 5\text{V}$ , $C_L = 150\text{ pF}$ $V_{CC} = 10\text{V}$ , $C_L = 150\text{ pF}$		85 40 95 45	160 80 210 110	ns ns ns ns
$t_{1H}$ , $t_{0H}$	Delay from Disable Input to High Impedance State, (from Logical "1" or Logical "0") MM70C95/MM80C95 MM70C96/MM80C96 MM70C97/MM80C97 MM70C98/MM80C98	$R_L = 10\text{k}$ , $C_L = 5\text{ pF}$ $V_{CC} = 5\text{V}$ $V_{CC} = 10\text{V}$ $V_{CC} = 5\text{V}$ $V_{CC} = 10\text{V}$ $V_{CC} = 5\text{V}$ $V_{CC} = 10\text{V}$ $V_{CC} = 5\text{V}$ $V_{CC} = 10\text{V}$		80 50 100 70 70 50 90 70	135 90 180 125 125 90 170 125	ns ns ns ns ns ns ns ns
$t_{H1}$ , $t_{H0}$	Delay from Disable Input to Logical "1" Level (from High Impedance State) MM70C95/MM80C95 MM70C96/MM80C96 MM70C97/MM80C97 MM70C98/MM80C98	$R_L = 10\text{k}$ , $C_L = 50\text{ pF}$ $V_{CC} = 5\text{V}$ $V_{CC} = 10\text{V}$ $V_{CC} = 5\text{V}$ $V_{CC} = 10\text{V}$ $V_{CC} = 5\text{V}$ $V_{CC} = 10\text{V}$ $V_{CC} = 5\text{V}$ $V_{CC} = 10\text{V}$		120 50 130 60 95 40 120 50	200 90 225 110 175 80 200 90	ns ns ns ns ns ns ns ns
$C_{IN}$	Input Capacitance	Any Input (Note 2)		5.0		pF
$C_{OUT}$	Output Capacitance TRI-STATE	Any Output (Note 2)		11		pF
$C_{PD}$	Power Dissipation Capacitance	(Note 3)		60		pF

\*AC Parameters are guaranteed by DC correlated testing.

## Truth Tables

MM70C95/MM80C95

Disable DIS <sub>1</sub>	Input DIS <sub>2</sub>	Input	Output
0	0	0	0
0	0	1	1
0	1	X	H-z
1	0	X	H-z
1	1	X	H-z

MM70C96/MM80C96

Disable DIS <sub>1</sub>	Input DIS <sub>2</sub>	Input	Output
0	0	0	1
0	0	1	0
0	1	X	H-z
1	0	X	H-z
1	1	X	H-z

MM70C97/MM80C97

Disable DIS <sub>4</sub>	Input DIS <sub>2</sub>	Input	Output
0	0	0	0
0	0	1	1
X	1	X	H-z*
1	X	X	H-z**

MM70C98/MM80C98









Disable DIS <sub>4</sub>	Input DIS <sub>2</sub>	Input	Output
0	0	0	1
0	0	1	0
X	1	X	H-z*
1	X	X	H-z**

\*Output 5–6 only

\*\*Output 1–4 only


X = Irrelevant

## AC Test Circuits and Switching Time Waveforms




**Note:** Delays measured with input  $t_r$ ,  $t_f \leq 20$  ns.


## Typical Performance Characteristics




TI /E/5907-5



TL/F/5907-6




TL/F/5907-7



TL/F/5907-8


## Schematic Diagrams

## MM70C95/MM80C95 TRI-STATE



TL/F/5907-9


## MM70C96/MM80C96 TRI-STATE



TL/F/5907-10


**Schematic Diagrams** (Continued)

**MM70C97/MM80C97 TRI-STATE**



TL/F/5907-11

**MM70C98/MM80C98 TRI-STATE**




TL/F/5907-12

The image contains three mechanical drawings of the J16A package:

- Top View:** Shows a rectangular package with 16 pins (8 on each long side). Dimensions include a total width of  $0.785 [19.94] \text{ MAX}$ , a pin pitch of  $0.025 [0.64]$ , and a pin diameter of  $0.005-0.020 \text{ TYP}$  [ $0.13-0.51$ ].
- Side View:** Shows the package height and pin profile. Dimensions include a maximum height of  $0.200 [5.08] \text{ MAX TYP}$ , a pin height of  $0.037 \pm 0.005$  [ $0.94 \pm 0.13$ ] TYP, and a pin thickness of  $0.015 [3.81] \text{ MIN TYP}$ . The pin angle is  $90^\circ \pm 4^\circ$  TYP.
- Detail View:** Shows the package with glass sealant. Dimensions include a sealant thickness of  $0.010 \pm 0.002$  [ $0.25 \pm 0.05$ ] TYP, a sealant width of  $0.180 [4.57] \text{ MAX}$ , and a package width of  $0.310-0.410$  [ $7.87-10.41$ ].

J16A (REV L)

## Physical Dimensions inches (millimeters) (Continued)



### Molded Dual-In-Line Package (N)

Order Number MM70C95N, MM70C96N, MM70C97N, MM70C98N,  
MM80C95N, MM80C96N, MM80C97N or MM80C98N

NS Package Number N16E

## LIFE SUPPORT POLICY

NATIONAL'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF THE PRESIDENT OF NATIONAL SEMICONDUCTOR CORPORATION. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and whose failure to perform, when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury to the user.
2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.



**National Semiconductor Corporation**  
1111 West Bardin Road  
Arlington, TX 76017  
Tel: 1(800) 272-9959  
Fax: 1(800) 737-7018

**National Semiconductor Europe**  
Fax: (+49) 0-180-530 85 86  
Email: onjwge@tevm2.nsc.com  
Deutsch Tel: (+49) 0-180-530 85 85  
English Tel: (+49) 0-180-532 78 32  
Français Tel: (+49) 0-180-532 93 58  
Italiano Tel: (+49) 0-180-534 16 80

**National Semiconductor Hong Kong Ltd.**  
13th Floor, Straight Block,  
Ocean Centre, 5 Canton Rd.  
Tsimshatsui, Kowloon  
Hong Kong  
Tel: (852) 2737-1600  
Fax: (852) 2736-9960

**National Semiconductor Japan Ltd.**  
Tel: 81-043-299-2309  
Fax: 81-043-299-2408